DATA SHEET SUSTAINABILITY

Sustainability data | Company data | Technical data

Basis 2023



COMPANY DATA

Company	Styrian family business with currently around 230 employees and sales of 1.7 million m ² (as of 2023)	Constant of the second s
Production	Multi-layer parquet in accordance with EN 13489 in three product series WOOD flor NOVOL OC® 5G, MULTIflor.11 NOVOLOC® 5G and BILAflor®.	
Product versions	Numerous types of wood, surface treatments as well as dimensions, structures and installation patterns as two or multi-layer parquet.	

SUSTAINABILITY DATA

EU-Ecolabel	SCHEUCHER is the first parquet manufacturer to meet the high requirements of the EU-ECOLABEL UZ035 flooring.	
Environmental Product Declaration	Our EPD no. EPD-SCP-20150324-EN, created in accordance with ISO 14025 and EN 15804, is published by IBU Germany and proves our sustainability in figures.	THE PARTY VIENE CONTRACTOR OF THE PARTY VIENE
LCA data for building certifications	The EPD lists the aggregated data for phases A1-A3 ("cradle to gate") C3 and D4, also available on BAUBOOK.at	DGNB BREEAM
TÜV ProfiCert Interior	The TÜV PROFICert certificate annually confirms that our products with the lowest emissions meet all European requirements.	
EUTR conformity	Scheucher fulfills all requirements of the European Timber Regula- tion and hereby confirms that no illegally logged wood is purchased or processed.	EUTR
DUE DILLIGENCE test Purchasing	Scheucher has commissioned the renowned institute "Global traca- bility solutions" with the due diligence audit in the area of Timber Legality Risk Assessment.	GLOBAL TRACEABILITY
FSC-CoC-Zertifikat	We have an FSC Chain of Custody certificate (HFA-CoC-100057), which confirms our separation of certified and non-certified wood.	First Constraints of the second secon
LEED Compliant	The LEED v4 specification for VOC emissions and FORMALDEHYD emissions from the USA (CDPH) is currently twice as strict as European limits.	LULLONG CONTROL OF CON
UKCA Compliant	Scheucher parquet may be marketed in Great Britain. The UKCA corresponds to a CE declaration and is mandatory in the UK	UK CA

CE labeling	The CE marking confirms compliance with the European minimum standards and is a prerequisite for placing this product on the market.	CE
TSCA Title VI compliant	We only use TSCA Title VI compliant plywood for the plywood end pieces (< 2 % by volume) compliant plywood and thus fulfill the CARB requirement in USA/Canada.	
FEP REALWOOD Program	Scheucher is a founding member of the FEP REALWOOD Program, with which products made of real wood are awarded.	Ver ralward ar
FEP REFINISHABLE CERTIFICATE	The FEP REAL WOOD REFINISHABLE CERTIFICATE confirms that our wear layer is suitable for repeated renovation through sanding and repairs.	TIP INT INT INT
30-year warranty	Scheucher grants a 30-year functional guarantee in the private sector (5 years in the public sector), please refer to our guarantee conditions.	30 JAHRE GRANTE



WOODflor NOVOLOC® 5G Multilayerparquet 14mm total thickness 3.6mm wear layer NOVOLOC® 5G connection



MULTIflor.11 NOVOLOC® 5G Multilayerparquet 11 mm total thickness 3.6mm wear layer NOVOLOC® 5G connection TONGUE/GROOVE connection



BILAflor 2-layer parquet 11 mm total thickness 3.6mm wear layer TONGUE/GROOVE connection

PRODUCT DATA

Surface treatment	Purely oxidative oiled/waxed (SEDA) or UV lacquered (TENSEO / PUROTEC)	Surface treatment	Sanded -sharp-edged , Valletta - brushed with bevel , Toskana - scraped , Valsega - b and-sawn and brushed, 4-sided bevel
SEDA PUROTEC TENSEO	TENSEO CLASSICO	Structures and haptics	
Connection	NOVOL OC® -5G Click connec- tion or Tongue/Groove- Connection	Sliding class	Depending on surface R9 or R10
Free from formaldehyde	Scheucher parquet does not contain any carcinogenic, biocidal or PCP-containing substances and is classified as formaldehyde-free!	Fire behavior	C _{fl} -s1 fully glued down, otherwise D _{fl} -s1
Load class	Highest class C according to	Load class SEDA	Suitability for commercial use,
TENSEO, PUROTEC	ÖNORM C2354		as deep impregnated
Underfloor heating system	Yes, suitable at 30-65% relati- ve humidity	Floor air conditioning	Yes, suitable. At least 25 °C surface temperature!
		Schaucher Holzindustrie GmbH	



Scheucher Holzindustrie GmbH, Zehensdorf 100, A-8092 Mettersdorf am Sassbach

+43 (0) 3477 2330 - 0 info@scheucherparkett.at | www.scheucherparkett.at